

Arena SUB 100P

10" (250mm) Powered Subwoofer







Black

White

Don't forget the bass.

We'd never build a JBL sound system and call it Arena without it packing powerful bass. With its 10" (250mm) high-output polycellulose woofer and dual rear ports that optimize bass performance, the JBL Arena SUB 100P plays its role to perfection. The 100W high-efficiency Class-D amplifier features unobtrusive rear-mounted controls that allow for easy setup and seamless integration into your sound system.

Features

- ► The signature punch and accuracy of JBL bass
- ► Understated, contemporary look and feel
- ► An audio powerhouse at an affordable price
- ➤ Just one part of an even more powerful



Arena SUB 100P

10" (250mm) Powered Subwoofer







Black

White

The signature punch and accuracy of JBL bass

10-inch (250mm) high-output polycellulose woofer with 100-watt RMS (200-watt dynamic) digital power amplifier. Dual rear ports optimize airflow while minimizing port turbulence and audible distortion in the bass response. Computer-optimized driver positioning and network integration. Variable level, crossover, and phase controls.

Understated, contemporary look and feel

Contemporary cabinet shape with angled side and top panels provide a sophisticated, modern look. Available in black and white finishes with minimalist grilles and brushed metal trims.

An audio powerhouse at an affordable price

The perfect trifecta of JBL power, precision, and affordable pricing.

Just one part of an even more powerful system

Intended for use in conjunction with the entire series of JBL Arena loudspeakers: 2 floorstanding speakers, 2 bookshelf speakers, 1 center channel speaker, and 1 subwoofer model. Features rear-mounted input and controls for easy set-up and system integration.

What's in the box:

1 x JBL Arena SUB 100P

1 x Power Cord

1 x Owner's Manual

1 x Safety Sheet

Product specifications:

- ► 10" (250mm) Polycellulose Low-Frequency Woofer
- ► Power: 100W RMS (200W Dynamic)
- ► Frequency Response: 41Hz 150Hz
- Crossover Frequencies: 50Hz 150Hz (variable)
 24 dB/octave
- ► Controls: Auto Power, Crossover, Level, Phase
- ► Input: One (1) Line-Level LFE Input
- ► Enclosure Type: Bass-Reflex via Rear-Firing Ports
- ► Power Requirement: 100V-240V, 50/60Hz
- Power Consumption (Idle/Full/Power):
 <0.5W (standby) / 160W/2.1A (max 120V) / 160W/1.5A (max – 230V)
- ► Dimensions (H x W x D): 14-5/16" x 14-1/2" x 16" 364mm x 368mm x 406mm
- ► Weight: 24 lbs (10.9 kg)

